



ENDUTEX - REVESTIMENTOS TEXTTEIS, SA

VIZELA / PORTUGAL



TECHNICAL DATA SHEET

REFERENCE: PRINT SX FR

DESCRIPTION: PVC DOUBLE COATED HIGH TENACITY POLYESTER FABRIC

COMPOSITION: 65 % PVC
35 % POLYESTER

WIDTH: 137 - 150 - 160 - 220 - 320 - 500 cm

| CHARACTERISTIC | SPECIFICATION | METHOD |
|---------------------------------|--------------------|----------------|
| THICKNESS (mm) | 0.35 | |
| TOTAL MASS (g/m ²) | 370 ± 30 | EN ISO 2286-2 |
| FABRIC MASS (g/m ²) | 130 ± 10 | EN ISO 2286-2 |
| BREAKING LOAD (daN/50mm) | L.: 250 T.: 140 | EN ISO 1421 |
| TEAR STRENGTH (daN) | L.: 25 T.: 20 | DIN 53363 |
| COATING ADHESION (daN/50mm) | min 5.0 | EN ISO 2411 |
| COLOUR FASTNESS TO LIGHT | min 6 | EN ISO 105-B02 |
| BURNING BEHAVIOUR | B1 | DIN 4102 |

L – Along T - Across

NOTE: This technical data sheet is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.

| Date | Revision | QUALITY CONTROL | TECHNICAL MANAGER |
|------------|----------|-----------------|-------------------|
| 2012.03.28 | 2 | | |