



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



## TECHNICAL DATA SHEET

**REFERENCE:** PRINT LT 40 M1

**DESCRIPTION:** PVC DOUBLE COATED HIGH TENACITY POLYESTER SCRIM WITH RELEASE LINER

**COMPOSITION:** 71 % PVC  
29 % POLYESTER

**WIDTH:** 110 - 137 - 160 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.53	
TOTAL MASS (g/m <sup>2</sup> )	330 ± 30 (Without Liner)	EN ISO 2286-2
FABRIC MASS (g/m <sup>2</sup> )	92 ± 10	EN ISO 2286-2
LINER MASS (g/m <sup>2</sup> )	120 ± 12	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 130 T.: 150	EN ISO 1421
TEAR STRENGTH (daN)	L.: 25 T.: 28	DIN 53363
COLOUR FASTNESS TO LIGHT	min 6	EN ISO 105-B02
AVERAGE PERMEABILITY OF FABRIC TO AIR (l/m <sup>2</sup> /s)	3300	EN ISO 9237
AVERAGE LIGHT TRANSMISSION	32.5	SF 600 Plus Spectrophotometer
BURNING BEHAVIOUR	M1	NF P92-503
OPEN AREA (%)	20	Internal

L - Along T - Across

**NOTE 1:** This technical data sheet is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied.

Purchaser is fully responsible for determining the product suitability for its intended application.

Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.

**NOTE 2:** The results do not include the release liner on the back side, as this one is removed after printing.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2012.04.10	3		