



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



certificação
acreditada
IFAC

TECHNICAL DATA SHEET

REFERENCE: PRINT LT 55 FR

DESCRIPTION : PVC DOUBLE COATED HIGH TENACITY POLYESTER SCRIM WITH
RELEASE LINER

COMPOSITION : 67 % PVC 33 % POLYESTER

WIDTH : 110 - 137 - 152 - 160 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.50	
TOTAL MASS (g/m ²)	350 ± 30 (Without Liner)	EN ISO 2286-2
FABRIC MASS (g/m ²)	115 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 130 T.: 170	EN ISO 1421
TEAR STRENGTH (daN)	L.: 25 T.: 35	DIN 53363
AVERAGE LIGHT TRANSMISSION	19.0	SF 600 Plus Spectrophotometer
AVERAGE PERMEABILITY OF FABRIC TO AIR (l/m ² /s)	1570	EN ISO 9237
BURNING BEHAVIOUR	M2	NF P92-503
BURNING BEHAVIOUR	B1	DIN 4102
BURNING BEHAVIOUR	Pass	NFPA 701
OPEN AREA (%)	10	Internal

L – Along T – Across

NOTE 1: This technical data sheet is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied.

Purchaser is fully responsible for determining the product suitability for its intended application.

Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.

NOTE 2: The results do not include the release liner on the backside, as this one is removed after printing.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2012.05.23	4		