



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



certificação  
acreditada  
IPAC

TECHNICAL DATA SHEET

**REFERENCE: PRINT LT 55 M1**

**DESCRIPTION** : PVC DOUBLE COATED HIGH TENACITY POLYESTER SCRIM WITH  
RELEASE LINER

**COMPOSITION** : 67 % PVC  
33 % POLYESTER

**WIDTH** : 110 - 137 - 152 - 160 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.50	
TOTAL MASS (g/m <sup>2</sup> )	350 ± 30 (Without Liner)	EN ISO 2286-2
FABRIC MASS (g/m <sup>2</sup> )	115 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 130 T.: 170	EN ISO 1421
TEAR STRENGTH (daN)	L.: 25 T.: 35	DIN 53363
AVERAGE LIGHT TRANSMISSION	19.0	SF 600 Plus Spectrophotometer
AVERAGE PERMEABILITY OF FABRIC TO AIR (l/m <sup>2</sup> /s)	1570	EN ISO 9237
BURNING BEHAVIOUR	M1	NF P92-503
OPEN AREA (%)	10	Internal

L – Along    T – Across

**NOTE 1** : This technical data sheet is not legal binding and is based on average results from current production. Unless otherwise stated, values cannot be considered as minimum to be satisfied. Purchaser is fully responsible for determining the product suitability for its intended application. Technical details are subject to change without prior notice, so please contact our technical service for any additional information you may require.

**NOTE 2** : The results do not include the release liner on the back side, as this one is removed after printing.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2012.05.23	4		