



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



---

---

TECHNICAL DATA SHEET

---

---

**REFERENCE:** PRINT 300 FR

**DESCRIPTION :** PVC DOUBLE COATED HIGH TENACITY POLYESTER WOVEN FABRIC

**COMPOSITION :** 73 % PVC  
27 % POLYESTER

**WIDTH :** 150 - 220 cm

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.30	
TOTAL MASS (g/m <sup>2</sup> )	330 ± 30	EN ISO 2286-2
FABRIC MASS (g/m <sup>2</sup> )	90 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 140 T.: 130	EN ISO 1421
BREAKING EXTENSION (%)	L.: 15 T.: 19	EN ISO 1421
TEAR STRENGTH (daN)	L.: 7.0 T.: 7.0	DIN 53363
COATING ADHESION (daN/50mm)	min. 5.0	EN ISO 2411
COLOUR FASTNESS TO LIGHT	min 6	EN ISO 105-B02
FLAMMABILITY (mm/min)	< 100	DIN 75200
BURNING BEHAVIOUR	B1	DIN 4102

L - Along  
T - Across

**NOTE :** Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2009.01.30	1		