



ENDUTEX - REVESTIMENTOS TEXTEIS, SA

VIZELA / PORTUGAL



---

---

TECHNICAL DATA SHEET

---

---

**REFERENCE: POLYCRIL 200 FR**

**DESCRIPTION : RESIN COATED POLYESTER WOVEN FABRIC**

**COMPOSITION : 22 % RESIN  
78 % POLYESTER**

**WIDTH : Up to 320 cm**

CHARACTERISTIC	SPECIFICATION	METHOD
THICKNESS (mm)	0.31	
TOTAL MASS (g/m <sup>2</sup> )	200 ± 20	EN ISO 2286-2
FABRIC MASS (g/m <sup>2</sup> )	155 ± 10	EN ISO 2286-2
BREAKING LOAD (daN/50mm)	L.: 130 T.: 100	EN ISO 1421
BREAKING EXTENSION (%)	L.: 25 T.: 25	EN ISO 1421
TEAR STRENGTH (daN)	L.: 3.0 T.: 5.0	EN ISO 4674-1B
BURNING BEHAVIOUR	B1	DIN 4102

L - Along T - Across

**NOTE : Unless otherwise stated, the figures presented shall be regarded as typical values for the material, and not as a minimum to be satisfied.**

Date	Revision	QUALITY CONTROL	TECHNICAL MANAGER
2009.07.31	0	<i>Amorali</i>	<i>[Signature]</i>